

THREE PHASE & DUAL MPPT

PV 6/8/10/12/15KTL

Application: Family Use



SUPERIOR EFFICIENCY

- Maximum efficiency 98.4%
- String current 13A, compatible with high power modules
- 150% PV configuration, 110% output overload



HIGH RELIABILITY

- Natural Cooling
- Die-cast aluminum case
- APP for local settings & display



INTELLIGENT MAINTENANCE

- Easy installation, light weight and small size
- Remote configuration and upgrade
- Supports export control



Model	PV 6KTL	PV 8KTL	PV 10KTL	PV 12KTL	PV 15KTL
Efficiency					
Max. Efficiency	98.2%	98.2%	98.4%	98.4%	98.4%
European Efficiency	97.8%	97.8%	98.0%	98.0%	98.0%
Input(PV)					
Max. Input Voltage	1000V				
Max. PV configuration (STC)	150%				
Rated Input Voltage	620V				
Max. Input Current	26A (2*13A)		39A (2*13A+13A)		
Max.Short Circuit Current	30A (2*15A)		45A(2*15A+15A)		
Start Input Voltage	200V				
MPPT Operating Voltage Range	160V-950V				
Max. Number of PV Strings	2(1/1)		3(2/1)		
No. of MPPTs	2				
Output(Grid)					
Rated AC Active Power	6,000W	8,000W	10,000W	12,000W	15,000W
Max. AC Apparent Power	6,600VA	8,800VA	11,000VA	13,200VA	16,500VA
Max. AC Active Power (PF=1)	6,600W	8,800W	11,000W	13,200W	16,500W
Max. AC Output Current	3*10A	3*13A	3*16A	3*18.2A	3*22.7A
Rated AC Voltage	380V/400V, 3W+N+PE				
AC Voltage Range ^①	277V-520V (adjustable)				
Rated Grid Frequency	50Hz / 60Hz				
Grid Frequency Range ^②	45Hz-55Hz / 55Hz-65Hz (Adjustable)				
THDI	<3% (Rated Power)				
DC Current Injection	<0.5In				
Power Factor	>0.99 Rated power (Adjustable 0.8 Leading-0.8 Lagging)				
Protection					
DC switch	Support				
Anti-islanding protection	Support				
AC overcurrent protection	Support				
AC short circuit protection	Support				
DC reverse connection	Support				
Surge Arrester	AC Type III				
Insulation detection	Support				
Leakage current protection	Support				
General					
Topology	Transformerless				
IP Rating	IP65				
Night Self Consumption	<1W				
Cooling	Natural cooling				
Operating Temperature Range	-25°C-60°C				
Relative Humidity Range	0-100%				
Max. Operating Altitude	4000m				
Noise	<30dB				
Dimensions (W*H*D)	400mm*500mm*190mm				
Weight	18.9kg		21.8kg		
HMI & COM					
Display	Wireless & APP+LED, LCD (Optional)				
Communication	RS485, WiFi / GPRS / 4G / LAN (Optional)				
Certification					
Safety	IEC62109-1, IEC62109-2				
Grid Code	IEC61727/62116				
Warranty	5 Years				

Remarks :

- ^{①②}The range of output voltage and frequency may vary depending upon different grid codes.
- Specifications are subject to change without advance notice.