

THREE PHASE & DUAL MPPT

PV 10/15KTL-D3/G2P, PV 17/20/22/25KTL-D3/G2

Application: Small-sized Industrial and Residential Use



SUPERIOR EFFICIENCY

- Maximum efficiency 98.4%
- Max String Current 20A, compatible with 600W+ modules
- 150% PV configuration, 110% output overload



HIGH RELIABILITY

- Die-cast aluminum case, IP66 waterproof and dustproof, C5 anti-corrosion
- DC /AC SPD, AFCI detection optional
- Compatible with wide power grid voltage and high harmonic power grid environment



INTELLIGENT MAINTENANCE

- App quick commissioning
- Remote configuration and upgrade
- Supports export control

Model	PV 10KTL-D3/G2P	PV 15KTL-D3/G2P	PV 17KTL-D3/G2	PV 20KTL-D3/G2	PV 22KTL-D3/G2	PV 25KTL-D3/G2
Efficiency						
Max. Efficiency	98.3%	98.4%	98.4%	98.4%	98.4%	98.4%
European Efficiency	97.8%	98.0%	98.0%	98.0%	98.0%	98.0%
Input (PV)						
Max. Input Voltage	1100V					
Max. PV configuration	150%					
Rated Input Voltage	620V					
Max. Input Current	30A+15A					2*30A
Max.Short Circuit Current	40A+20A					2*40A
Start Input Voltage	180V					
MPPT Operating Voltage Range	160V-1000V					
Max. Number of PV Strings	3 (2/1)					4 (2/2)
No. of MPPTs	2					
Output (Grid)						
Rated AC Active Power	10,000W	15,000W	17,000W	20,000W	22,000W	25,000W
Rated Apparent Power	10,000VA	15,000VA	17,000VA	20,000VA	22,000VA	25,000VA
Max. AC Apparent Power	11,000VA	16,500VA	18,700VA	22,000VA	24,200VA	25,000VA
Max. AC Active Power (PF=1)	11,000W	16,500W	18,700W	22,000W	24,200W	25,000W
Max. AC Output Current	3*16.8A	3*25.3A	3*28.6A	3*33.7A	3*37A	3*39.8A
Rated AC Voltage	380V / 400V / 415V, 3W+N+PE					
AC Voltage Range ^①	260V-510V (Adjustable)					
Rated Grid Frequency	50Hz / 60Hz					
Grid Frequency Range ^②	45Hz-55Hz / 55Hz-65Hz (Adjustable)					
THDI	<3%@Rated Power					
DC Current Injection	<0.5%@Rated Current					
Power Factor	> 0.99 Rated power (Adjustable 0.8 LD - 0.8 LG)					
Protection						
DC switch	Support					
Anti-islanding protection	Support					
AC overcurrent protection	Support					
AC short circuit protection	Support					
DC reverse connection	Support					
Surge Arrester	AC Type III (Type II optional) / DC Type III (Type II optional)					
Insulation detection	Support					
String current detection	Optional					
Leakage current protection	Support					
General						
Topology	Transformerless					
IP Rating	IP66					
Night Self Consumption	<1W					
Cooling	Natural cooling					Fan cooling
Operating Temperature Range	-25°C-60°C					
Relative Humidity Range	0-100%					
Max. Operating Altitude	4000m					
Noise	<45dB					
Dimensions (W*H*D)	398mm*460mm*190mm					
Weight	23Kg					
HMI & COM						
Display	Wireless & APP +LED, LCD (Optional)					
Communication	RS485, Optional: WiFi / GPRS / 4G					
Certification						
Safety	IEC62109-1, IEC62109-2					
Grid Code	VDE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206006/206007-1, UNE 217001, IEC 61727/62116, AS 4777					
Warranty	10 Years					

Remarks : • ^{①②}The range of output voltage and frequency may vary depending upon different grid codes.
• Specifications are subject to change without advance notice.